













QolorFLEX LED Tape Specifications

Product Image	Product Name	Part Number	Operating Voltage	Use Environment	Color(s)	Length	Width	Weight (Kg)	Cutting Increment	LED Spacing	Backing Color	Material	Color Temperature	Wavelength	Beam Angle	Brightness	Color Rendering Index (CRI)	Current (A/5m)	Power Consumption (w/5m)	Power Consumption (w/ft)	Density (LEDs/m)	LED Chip Size	Dimmable	Warranty	Average Life	IP Rating	Compliance	Description	Cut Sheet link
24V Indoor:																													
QolorFLEX® HIQ High CRI LED Tape, 24V Indoor:																													
	QolorFLEX® HIQ High CRI LED Tape, 2700-6500K	3527-24-H27006500-120-5-20-1	24VDC	Indoor	Warm White & Cool White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	50.0 mm (1.965 in)	8.3mm (0.33 in)	White	LED Tape	2700K±150K, 6500K±500K	N/A	120°	1200 lumens/m	≥ 95	3.2A	77 w/5m	4.69 w/ft	120 LEDs/m	3527	Fully Dimmable	Two years	50,000 hours	IP20	ETL, CE, RoHS	QolorFLEX HIQ High CRI LED Tape, 2700-6500K (P/N 3527-24-H27006500-120-5-20-1) was designed to have a Color Rendering Index (CRI) of 95+, making it an ideal high CRI LED tape for the needs of the film industry. Tungsten 2700 to Daylight 6500K in a single chip offers exceptional on-camera color rendition and the ability to match the Daylight and Tungsten light sources already being used on film and television sets.	https://www.citytheatrical.com/docs/default-source/cut-sheets/3527-24-h27006500-120-5-20-1.pdf
	QolorFLEX® HIQ High CRI LED Tape, 3200K	2835-24-H3200-120-5-20-1	24VDC	Indoor	Warm White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	50.0 mm (1.965 in)	8.3mm (0.33 in)	White	LED Tape	3200K ± 200K	N/A	120°	1200 lumens/m	≥ 95	2.6A	63 w/5m	3.8 w/ft	120 LEDs/m	2835	Fully Dimmable	Two years	50,000 hours	IP20	ETL, CE, RoHS	QolorFLEX HIQ High CRI LED Tape, 3200K (P/N 2835-24-H3200-120-5-20-1) was designed to have a Color Rendering Index (CRI) of 95+, making it an ideal high CRI LED tape for the needs of the film industry. QolorFLEX HIQ High CRI LED Tape, 3200K offers exceptional on-camera color rendition and the ability to match the Tungsten light sources already being used on film and television sets.	https://www.citytheatrical.com/docs/default-source/cut-sheets/2835-24-h3200-120-5-20-1.pdf
	QolorFLEX® HIQ High CRI LED Tape, 6000K	2835-24-H6000-120-5-20-1	24VDC	Indoor	Cool White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	50.0 mm (1.965 in)	8.3mm (0.33 in)	White	LED Tape	6000K ± 200K	N/A	120°	1200 lumens/m	≥ 95	2.6A	63 w/5m	3.8 w/ft	120 LEDs/m	2835	Fully Dimmable	Two years	50,000 hours	IP20	ETL, CE, RoHS	QolorFLEX HIQ High CRI LED Tape, 6000K (P/N 2835-24-H6000-120-5-20-1) was designed to have a Color Rendering Index (CRI) of 95+, making it an ideal high CRI LED tape for the needs of the film industry. QolorFLEX HIQ High CRI LED Tape, 6000K offers exceptional on-camera color rendition and the ability to match the Daylight light sources already being used on film and television sets.	https://www.citytheatrical.com/docs/default-source/cut-sheets/2835-24-h6000-120-5-20-1.pdf
QolorFLEX® 5-in-1 LED Tape, 24V Indoor:																													
	QolorFLEX® 5-in-1 LED Tape, HIQ High CRI	5050-24-RGBH27006500-60-5-20-1	24VDC	Indoor	RGB+WW+CW	5m (16.404 ft)	12mm (0.472 in)	0.12 Kg	100 mm (3.937 in)	16.7mm (0.657 in)	White	LED Tape	2700 K, 6500 K	622/522/468 nm	120°	960 lumens/m	>95	2.5A	72 w/5m	4.39 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	30,000 hours	IP20	ETL, CE, RoHS	QolorFLEX 5-in-1 LED Tape, HIQ High CRI (P/N 5050-24-RGBH27006500-60-5-20-1) is an interior grade 5-in-1 24V RGB + Tunable White LED Tape with a Color Rendering Index (CRI) of 95. It is 25% brighter than other 5-in-1 LED tapes, making it an ideal high CRI LED tape for the camera needs of film and video projects, while providing lighting professionals with ultimate color control. It offers exceptional on-camera color rendition and the ability to match the light sources already being used on set. It can create a wide spectrum of colors using red, blue, green, and tunable 2700K to 6500K white.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-rgbh27006500-60-5-20-1.pdf
	QolorFLEX® 5-in-1 LED Tape, RGB + Amber + Cool White	5050-24-RGBACW-60-5-20-1	24VDC	Indoor	RGB+A+CW	5m (16.404 ft)	12mm (0.472 in)	0.12 Kg	100mm (3.937 in)	16.7mm (0.657 in)	White	LED Tape	6500K ± 500K	622/518/468/588	120°	700 lumens/m	≥80	2.5A	60 w/5m	3.66 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	50,000 hours	IP20	ETL, CE, RoHS	QolorFLEX 5-in-1 LED Tape, RGB + Amber + Cool White (P/N 5050-24-RGBACW-60-5-20-1) is an interior grade 5-in-1 24V RGBACW LED Tape with high output brightness and the ability to create a wide spectrum of colors when used with a DMX color control system. Ideal for installations for television and film, all LEDs used in QolorFLEX 5-in-1 LED Tape RGBACW are identical to create a more even illumination.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-rgbacw-60-5-20-1.pdf
QolorFLEX® Quad Chip Plus Deep Red LED Tape, 24V Indoor:																													
	QolorFLEX® Quad Chip LED Tape, RGB Amber Plus Deep Red	5050-24-RGBAD-60-5-20-1	24VDC	Indoor	RGB Amber + Deep Red	5m (16.404 ft)	12mm (0.47 in)	0.12 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	N/A	622/518/468/588/660	120°	455 lumens/m	N/A	2.5A	70 w/5m	4.27 w/ft	60 LEDs/m	5050 + 2835	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX Quad Chip RGBA + Deep Red LED Tape (P/N 5050-24-RGBAD-60-5-20-1) is an interior grade 24V Quad Chip 4-in-1 RGBA plus Deep Red LED tape with a high output brightness and the ability to create a wide spectrum of colors when used with a DMX color control system. This is the ideal LED tape for lighting designers looking for a true red color. It can be used in film, video and theatrical applications and is available in full 5 meter reels and sample strips.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-rgbad-60-5-20-1.pdf
QolorFLEX® Quad Chip LED Tape, 24V Indoor:																													
	QolorFLEX® Quad Chip LED Tape, RGB + Amber	5050-24-Q-RGBA-60-5-20-1	24VDC	Indoor	RGB + Amber	5m (16.404 ft)	12mm (0.47 in)	0.12 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	N/A	622/518/468/588	120°	560 lumens/m	N/A	2.5A	60 w/5m	3.66 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, Quad Chip RGB + Amber (P/N 5050-24-Q-RGBA-60-5-20-1) is an interior grade 24V Quad Chip 4-in-1 Red + Green + Blue + Amber LED Tape.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-q-rgb-60-5-20-1.pdf
	QolorFLEX® Quad Chip LED Tape, RGB + Indigo	5050-24-Q-RGBI-60-5-20-1	24VDC	Indoor	RGB + Indigo	5m (16.404 ft)	12mm (0.47 in)	0.12 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	N/A	622/518/468/450	120°	480 lumens/m	N/A	2.5A	60 w/5m	3.66 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX Quad Chip LED Tape, RGB + Indigo (P/N 5050-24-Q-RGBI-60-5-20-1) is an interior grade 24V Quad Chip 4-in-1 Red + Green + Blue + Indigo LED Tape.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-q-rgb-60-5-20-1.pdf
	QolorFLEX® Quad Chip LED Tape, RGB + Cool White	5050-24-Q-RGBCW-60-5-20-1	24VDC	Indoor	RGB + Cool White	5m (16.404 ft)	12mm (0.47 in)	0.12 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	N/A	622/518/468/6500*K	120°	400 lumens/m	80	2.5A	60 w/5m	3.66 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX Quad Chip LED Tape, RGB + Cool White (P/N 5050-24-Q-RGBCW-60-5-20-1) is an interior grade 24V Quad Chip 4-in-1 Red + Green + Blue + Cool White LED Tape.	https://www.citytheatrical.com/docs/default-source/cut-sheets/qolorflex-tape-pn-5050-q-24-rgbww-60-5-20-1.pdf
	QolorFLEX® Quad Chip LED Tape, RGB + Warm White	5050-24-Q-RGBWW-60-5-20-1	24VDC	Indoor	RGB + Warm White	5m (16.404 ft)	12mm (0.47 in)	0.12 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	N/A	622/518/468/2700*K	120°	700 lumens/m	80	2.5A	60 w/5m	3.66 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX Quad Chip LED Tape, RGB + Warm White (P/N 5050-24-Q-RGBWW-60-5-20-1) is an interior grade 24V Quad Chip 4-in-1 Red + Green + Blue + Warm White LED Tape.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-q-rgbww-60-5-20-1.pdf
QolorFLEX® RGB and X LED Tape, 24V Indoor:																													
	QolorFLEX® LED Tape, 24V Indoor, RGB and Cool White	5050-24-RGBCW-60-5-20-1	24VDC	Indoor	RGB + Cool White	5m (16.404 ft)	12mm (0.47 in)	0.12 Kg	170.00mm (6.69 in)	16.7mm (0.657 in)	White	LED Tape	6500* K	622/518/468	120°	400 lumens/m	N/A	2.1A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 24V Indoor, RGB and Cool White (P/N 5050-24-RGBCW-60-5-20-1) is an interior grade 24V Red + Green + Blue + Cool White LED tape.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-rgbww-60-5-20-1.pdf
QolorFLEX® RGB LED Tape, 24V Indoor:																													
	QolorFLEX® LED Tape, 24V Indoor, RGB	5050-24-RGB-60-5-20-1	24VDC	Indoor	RGB	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	N/A	622/518/468	120°	350 lumens/m	N/A	2.1A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 24V Indoor, RGB (P/N 5050-24-RGB-60-5-20-1) is an interior grade 24V Red + Green + Blue LED Tape.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-rgb-60-5-20-1-cut-sheet.pdf
QolorFLEX® UV LED Tape, 24V Indoor:																													

QolorFLEX LED Tape Specifications

Product Image	Product Name	Part Number	Operating Voltage	Use Environment	Color(s)	Length	Width	Weight (Kg)	Cutting Increment	LED Spacing	Backing Color	Material	Color Temperature	Wavelength	Beam Angle	Brightness	Color Rendering Index (CRI)	Current (A/5m)	Power Consumption (w/5m)	Power Consumption (w/ft)	Density (LEDs/m)	LED Chip Size	Dimmable	Warranty	Average Life	IP Rating	Compliance	Description	Cut Sheet link
	QolorFLEX® UV LED Tape, 24V Indoor	2835-24-UV395-60-5-20-1	24VDC	Indoor	UV	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	N/A	395 nm	120°	N/A	≥ 95	1.5A	36 w/5m	2.19 w/ft	60 LEDs/m	2835	Fully Dimmable	Two years	50,000 hours	IP20	ETL, CE, RoHS	QolorFLEX UV LED Tape (P/N 2835-24-UV395-60-5-20-1) provides a "glow in the dark" effect.	https://www.citytheatrical.com/docs/default-source/cut-sheets/2835-24-uv395-60-5-20-1.pdf
QolorFLEX® LED Tape, 24V Indoor, White:																													
	QolorFLEX® LED Tape, 24V Indoor, Adjustable White	3528-24-WWCW-120-5-20-1	24VDC	Indoor	Warm White & Cool White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	100.00 mm (3.94 in)	8.3mm (0.33 in)	White	LED Tape	2,400° - 6,500° K	N/A	120°	635/753 lumens/m	70	3.5A	84 w/5m	5.10 w/ft	120 LEDs/m	3528	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 24V Indoor, Adjustable White (P/N 3528-24-WWCW-120-5-20-1) is an interior grade adjustable white LED Tape with a high output brightness and the ability to vary the color temperature from very warm (2400°K) to daylight (6500°K) when used with a DMX control system. Its 24V configuration allows for longer runs. It is available in full 5 metre reels.	https://www.citytheatrical.com/docs/default-source/cut-sheets/3528-24-wcw-120-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 24V Indoor, Cool White	5050-24-CW-60-5-20-1	24VDC	Indoor	Cool White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	6500° K	N/A	120°	1030 lumens/m	70	2.1A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 24V Indoor, Cool White (P/N 5050-24-CW-60-5-20-1) is an interior grade 24V LED Tape with a high output (1030 lumens/metre) brightness. The cool white color (6500°K) accentuates blue and subdues green and red.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-cw-60-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 24V Indoor, Natural White	5050-24-NW-60-5-20-1	24VDC	Indoor	Natural White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	4100° K	N/A	120°	990 lumens/m	70	2.1A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 24V Indoor, Natural White (P/N 5050-24-NW-60-5-20-1) is an interior grade 24V LED Tape with a high output (900 lumens/metre) brightness. The natural white color (4100°K) makes it perfect for displays or light box use, where good color rendition is needed.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-nw-60-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 24V Indoor, Warm White	5050-24-WW-60-5-20-1	24VDC	Indoor	Warm White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	2700° K	N/A	120°	900 lumens/m	70	2.1A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 24V Indoor, Warm White (P/N 5050-24-WW-60-5-20-1) is an interior grade 24V LED Tape with a high output (900 lumens/metre) brightness. The warm white color (2700°K) makes it useful for enhancing skin tones.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-ww-60-5-20-1-cut-sheet.pdf
24V Outdoor:																													
QolorFLEX NuNeon® Linear Lighting, 24V Outdoor:																													
	QolorFLEX NuNeon®, RGB	N914-RGB-5	24VDC	Indoor / Outdoor	RGB	5m (16.404 ft)	9mm (0.354 in)	0.98 Kg	50mm (1.969 in)	7.14mm (0.281 in)	White Finish	Silicone Extrusion	N/A	622/518/468 nm	120°	330 lumens/m	N/A	2.0A	48w/5m	2.93 w/ft	140 LEDs/m	3528	Fully Dimmable	Two years	50,000 hours	IP67	ETL, CE, RoHS	QolorFLEX NuNeon, RGB (P/N N914-RGB-5) is a sealed LED linear product that is flexible and safe for indoor or outdoor use. QolorFLEX NuNeon, RGB provides three-color Red + Blue + Green color blending, a brightness of 330 lumens/m, and is available in 5m reels.	https://www.citytheatrical.com/docs/default-source/cut-sheets/n914-rgb-5-cut-sheet.pdf
	QolorFLEX NuNeon®, Amber	N914-A-10	24VDC	Indoor / Outdoor	Amber	10m (32.808 ft)	9mm (0.354 in)	1.63 Kg	50mm (1.969 in)	7.14mm (0.281 in)	White Finish	Silicone Extrusion	N/A	588 nm	120°	150 lumens/m	N/A	3.0A	36w/5m	2.2 w/ft	140 LEDs/m	2835	Fully Dimmable	Two years	50,000 hours	IP67	ETL, CE, RoHS	QolorFLEX NuNeon, Amber (P/N N914-A-10) is a sealed LED linear product that is flexible and safe for indoor or outdoor use. QolorFLEX NuNeon, Amber provides single color amber light with a brightness of 150 lumens/m, and is available in 10m reels.	https://www.citytheatrical.com/docs/default-source/cut-sheets/n914-a-10-cut-sheet.pdf
	QolorFLEX NuNeon®, Red	N914-R-10	24VDC	Indoor / Outdoor	Red	10m (32.808 ft)	9mm (0.354 in)	1.63 Kg	50mm (1.969 in)	7.14mm (0.281 in)	White Finish	Silicone Extrusion	N/A	622 nm	120°	200 lumens/m	N/A	3.0A	36w/5m	2.2 w/ft	140 LEDs/m	2835	Fully Dimmable	Two years	50,000 hours	IP67	ETL, CE, RoHS	QolorFLEX NuNeon, Red (P/N N914-R-10) is a sealed LED linear product that is flexible and safe for indoor or outdoor use. QolorFLEX NuNeon, Red provides single color red light with a brightness of 200 lumens/m, and is available in 10m reels.	https://www.citytheatrical.com/docs/default-source/cut-sheets/n914-r-10-cut-sheet.pdf
	QolorFLEX NuNeon®, Green	N914-G-10	24VDC	Indoor / Outdoor	Green	10m (32.808 ft)	9mm (0.354 in)	1.63 Kg	50mm (1.969 in)	7.14mm (0.281 in)	White Finish	Silicone Extrusion	N/A	518 nm	120°	650 lumens/m	N/A	3.0A	36w/5m	2.2 w/ft	140 LEDs/m	2835	Fully Dimmable	Two years	50,000 hours	IP67	ETL, CE, RoHS	QolorFLEX NuNeon, Green (P/N N914-G-10) is a sealed LED linear product that is flexible and safe for indoor or outdoor use. QolorFLEX NuNeon, Green provides single color green light with a brightness of 650 lumens/m, and is available in 10m reels.	https://www.citytheatrical.com/docs/default-source/cut-sheets/n914-g-10-cut-sheet.pdf
	QolorFLEX NuNeon®, Blue	N914-B-10	24VDC	Indoor / Outdoor	Blue	10m (32.808 ft)	9mm (0.354 in)	1.63 Kg	50mm (1.969 in)	7.14mm (0.281 in)	White Finish	Silicone Extrusion	N/A	468 nm	120°	85 lumens/m	N/A	3.0A	36w/5m	2.2 w/ft	140 LEDs/m	2835	Fully Dimmable	Two years	50,000 hours	IP67	ETL, CE, RoHS	QolorFLEX NuNeon, Blue (P/N N914-B-10) is a sealed LED linear product that is flexible and safe for indoor or outdoor use. QolorFLEX NuNeon, Blue provides single color blue light with a brightness of 85 lumens/m, and is available in 10m reels.	https://www.citytheatrical.com/docs/default-source/cut-sheets/n914-b-10.pdf
	QolorFLEX NuNeon®, Tunable White HiQ High CRI	N914-H27006500-5	24VDC	Indoor / Outdoor	Warm White / Cool White	5m (16.404 ft)	9mm (0.354 in)	0.98 Kg	50mm (1.969 in)	7.14mm (0.281 in)	White Finish	Silicone Extrusion	2700 K, 6500 K	N/A	120°	600 lm/m	> 94	2.9A	70w/5m	4.27 w/ft	240 LEDs/m	2835	Fully Dimmable	Two years	50,000 hours	IP67	ETL, CE, RoHS	QolorFLEX NuNeon, Tunable White HiQ High CRI (P/N N914-H27006500-5) is a sealed LED linear product that is flexible and safe for indoor or outdoor use. QolorFLEX NuNeon, Tunable White HiQ High CRI offers exceptional on-camera color rendition with a Color Rendering Index (CRI) greater than 94, allowing lighting professionals to meet the needs of high quality film and video lighting. It has a color temperature ranging from 2700 K to 6500 K, a brightness of 600 lumens/m, and is available in 5m reels.	https://www.citytheatrical.com/docs/default-source/cut-sheets/n914-h27006500-5.pdf
	QolorFLEX NuNeon®, Cool White	N914-CW-10	24VDC	Indoor / Outdoor	Cool White	10m (32.808 ft)	9mm (0.354 in)	1.63 Kg	50mm (1.969 in)	7.14mm (0.281 in)	White Finish	Silicone Extrusion	6500 K	N/A	120°	650 lm/m	N/A	3.0A	36w/5m	2.2 w/ft	140 LEDs/m	2835	Fully Dimmable	Two years	50,000 hours	IP67	ETL, CE, RoHS	QolorFLEX NuNeon, Cool White (P/N N914-CW-10) is a sealed LED linear product that is flexible and safe for indoor or outdoor use. QolorFLEX NuNeon, Cool White provides single color cool white light with a brightness of 650 lumens/m, and is available in 10m reels.	https://www.citytheatrical.com/docs/default-source/cut-sheets/n914-cw-10-cut-sheet.pdf
	QolorFLEX NuNeon®, Natural White	N914-NW-10	24VDC	Indoor / Outdoor	Natural White	10m (32.808 ft)	9mm (0.354 in)	1.63 Kg	50mm (1.969 in)	7.14mm (0.281 in)	White Finish	Silicone Extrusion	4000 K	N/A	120°	750 lm/m	N/A	3.0A	36w/5m	2.2 w/ft	140 LEDs/m	2835	Fully Dimmable	Two years	50,000 hours	IP67	ETL, CE, RoHS	QolorFLEX NuNeon, Natural White (P/N N914-NW-10) is a sealed LED linear product that is flexible and safe for indoor or outdoor use. QolorFLEX NuNeon, Natural White provides single color natural white light with a brightness of 750 lumens/m, and is available in 10m reels.	https://www.citytheatrical.com/docs/default-source/cut-sheets/n914-nw-10-cut-sheet.pdf






QolorFLEX LED Tape Specifications

Product Image	Product Name	Part Number	Operating Voltage	Use Environment	Color(s)	Length	Width	Weight (Kg)	Cutting Increment	LED Spacing	Backing Color	Material	Color Temperature	Wavelength	Beam Angle	Brightness	Color Rendering Index (CRI)	Current (A/5m)	Power Consumption (w/5m)	Power Consumption (w/ft)	Density (LEDs/m)	LED Chip Size	Dimmable	Warranty	Average Life	IP Rating	Compliance	Description	Cut Sheet link
	QolorFLEX NuNeon®, Warm White	N914-WW-10	24VDC	Indoor / Outdoor	Warm White	10m (32.808 ft)	9mm (0.354 in)	1.63 Kg	50mm (1.969 in)	7.14mm (0.281 in)	White Finish	Silicone Extrusion	2700 K	N/A	120°	750 lm/m	N/A	3.0A	36w/5m	2.2 w/ft	140 LEDs/m	2835	Fully Dimmable	Two years	50,000 hours	IP67	ETL, CE, RoHS	QolorFLEX NuNeon, Warm White (P/N N914-WW-10) is a sealed LED linear product that is flexible and safe for indoor or outdoor use. QolorFLEX NuNeon, Warm White provides single color warm white light with a brightness of 750 lumens/m, and is available in 10m reels.	https://www.citytheatrical.com/docs/default-source/cut-sheets/n914-ww-10-cut-sheet.pdf
QolorFLEX® LED Tape, 24V Outdoor:																													
	QolorFLEX® LED Tape, 24V Outdoor, RGB	5050-24-RGB-60-5-67-1	24VDC	Outdoor	RGB	5m (16.404 ft)	12.2mm (0.48 in)	0.24 Kg	100.0 mm (3.93 in)	16.7mm (0.657 in)	White	Silicone sleeve	N/A	622/518/468	120°	350 lumens/m	N/A	2.1A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP67	ETL, CE, RoHS	QolorFLEX LED Tape, 24V Outdoor, RGB (P/N 5050-24-RGB-60-5-67-1) is an exterior grade 24V RGB LED Tape with a high output brightness and the ability to create a wide spectrum of colors when used with a DMX color control system.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-rgb-60-5-67-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 24V Outdoor, Adjustable White	3528-24-WWCW-120-5-67-1	24VDC	Outdoor	Adjustable White	5m (16.404 ft)	12.2mm (0.48 in)	0.24 Kg	100.0 mm (3.93 in)	8.3 mm (0.33 in)	White	Silicone sleeve	2400° K - 6500° K	N/A	120°	635/753 lumens/m	70	3.5A	84 w/5m	5.10 w/ft	120 LEDs/m	3528	Fully Dimmable	Two years	25,000 hours	IP67	ETL, CE, RoHS	QolorFLEX LED Tape, 24V Outdoor, Adjustable White (P/N 3528-24-WWCW-120-5-67-1) is an exterior grade adjustable white LED Tape encased in a translucent waterproof silicone sleeve. It has an IP rating of 67 and the ability to vary the color temperature from very warm (2400°K) to daylight (6500°K) when used with a DMX control system.	https://www.citytheatrical.com/docs/default-source/cut-sheets/3528-24-wwcw-120-5-67-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 24V Outdoor, Cool White	5050-24-CW-60-5-67-1	24VDC	Outdoor	Cool White	5m (16.404 ft)	12.2mm (0.48 in)	0.24 Kg	100 mm (3.937 in)	16.7mm (0.657 in)	White	Silicone sleeve	6500° K	N/A	120°	1,030 lumens/m	70	2.1A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP67	ETL, CE, RoHS	QolorFLEX LED Tape, 24V Outdoor, Cool White (P/N 5050-24-CW-60-5-67-1) is an exterior grade 24V LED Tape encased in a translucent waterproof silicone sleeve. It has an IP rating of 67 and a high output (1030 lumens/metre) brightness. The cool white color (6500°K) accentuates blues and subdues greens and reds.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-cw-60-5-67-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 24V Outdoor, Natural White	5050-24-NW-60-5-67-1	24VDC	Outdoor	Natural White	5m (16.404 ft)	12.2mm (0.48 in)	0.24 Kg	100 mm (3.937 in)	16.7mm (0.657 in)	White	Silicone sleeve	4100° K	N/A	120°	990 lumens/m	70	2.1A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP67	ETL, CE, RoHS	QolorFLEX LED Tape, 24V Outdoor, Natural White (P/N 5050-24-NW-60-5-67-1) is an exterior grade 24V LED Tape encased in a translucent waterproof silicone sleeve. It has an IP rating of 67 and a high output (990 lumens/metre) brightness.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-nw-60-5-67-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 24V Outdoor, Warm White	5050-24-WW-60-5-67-1	24VDC	Outdoor	Warm White	5m (16.404 ft)	12.2mm (0.48 in)	0.24 Kg	100 mm (3.937 in)	16.7mm (0.657 in)	White	Silicone sleeve	2700° K	N/A	120°	900 lumens/m	70	2.1A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP67	ETL, CE, RoHS	QolorFLEX LED Tape, 24V Outdoor, Warm White (P/N 5050-24-WW-60-5-67-1) is an exterior grade 24V LED Tape encased in a clear waterproof silicone sleeve. It has an IP rating of 67 has a high output (900 lumens/metre) brightness.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-24-ww-60-5-67-1-cut-sheet.pdf
12V Indoor:																													
QolorFLEX® RGB and X LED Tape, 12V Indoor:																													
	QolorFLEX® LED Tape, 12V Indoor, RGB and Amber	5050-12-RGBA-60-5-20-1	12VDC	Indoor	RGB & Amber	5m (16.404 ft)	12mm (0.47 in)	0.24 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	N/A	622/518/468/588	120°	400 lumens/m	N/A	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, RGB and Amber (P/N 5050-12-RGBA-60-5-20-1) is an interior grade hybrid LED Tape with a medium output brightness. The combination of RGB and amber LEDs allow for precise color mixing.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-rgba-60-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Indoor, RGB and Indigo	5050-12-RGBI-60-5-20-1	12VDC	Indoor	RGB & Indigo	5m (16.404 ft)	12mm (0.47 in)	0.24 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	N/A	622/518/468/450	120°	400 lumens/m	N/A	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, RGB and Indigo (P/N 5050-12-RGBI-60-5-20-1) is an interior grade hybrid LED Tape with a high output brightness. The combination of RGB and indigo LEDs allow for precise color mixing.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-rgb-i-60-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Indoor, RGB and Cool White	5050-12-RGBCW-60-5-20-1	12VDC	Indoor	RGB & Cool White	5m (16.404 ft)	12mm (0.47 in)	0.24 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	N/A	622/518/468/6500°K	120°	515 lumens/m	N/A	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, RGB and Cool White (P/N 5050-12-RGBCW-60-5-20-1) is an interior grade hybrid LED Tape with a high output brightness. The combination of RGB and Cool white LEDs allow for precise color mixing.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-rgb-cw-60-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Indoor, RGB and Natural White	5050-12-RGBNW-60-5-20-1	12VDC	Indoor	RGB & Natural White	5m (16.404 ft)	12mm (0.47 in)	0.24 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	N/A	622/518/468/4100°K	120°	400 lumens/m	N/A	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, RGB and Natural White (P/N 5050-12-RGBNW-60-5-20-1) is an interior grade hybrid LED Tape with a high output brightness. The combination of RGB and natural white LEDs allow for precise color mixing.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-rgb-nw-60-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Indoor, RGB and Warm White	5050-12-RGWW-60-5-20-1	12VDC	Indoor	RGB & Warm White	5m (16.404 ft)	12mm (0.47 in)	0.24 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	LED Tape	N/A	622/518/468/2700°K	120°	400 lumens/m	70	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, RGB and Warm White (P/N 5050-12-RGWW-60-5-20-1) is an interior grade hybrid LED Tape with a high output brightness. The combination of RGB and warm white LEDs enable a warmer range of colors for enhancing skin tones.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-rgb-ww-60-5-20-1-cut-sheet.pdf
QolorFLEX® RGB LED Tape, 12V Indoor:																													
	QolorFLEX® LED Tape, 12V Indoor, RGB	5050-12-RGB-60-5-20-1	12VDC	Indoor	RGB	5m (16.404 ft)	10mm (0.394 in)	0.14 Kg	50.0 mm (1.965 in)	16.7mm (0.657 in)	White	LED Tape	N/A	622/518/468	120°	350 lumens/m	N/A	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, RGB (P/N 5050-12-RGB-60-5-20-1) is an interior grade Red + Green + Blue LED Tape with a high output brightness.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-rgb-60-5-20-1-cut-sheet.pdf
QolorFLEX® Cool White LED Tape, 12V Indoor:																													
	QolorFLEX® LED Tape, 12V Indoor, Cool White (High Output, 1030 lumens/metre)	5050-12-CW-60-5-20-1	12VDC	Indoor	Cool White	5m (16.404 ft)	10mm (0.394 in)	0.14 Kg	50.0 mm (1.965 in)	16.7mm (0.657 in)	White	LED Tape	6500° K	N/A	120°	1030 lumens/m	70	2.1A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, Cool White (High Output, 1030 lumens/metre) (P/N 5050-12-CW-60-5-20-1) is an interior grade LED tape with a high output (1030 lumens/metre) brightness. The cool white color (6500°K) is suited for enhancing the blue color range.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-cw-60-5-20-1-cut-sheet.pdf

QolorFLEX LED Tape Specifications

Product Image	Product Name	Part Number	Operating Voltage	Use Environment	Color(s)	Length	Width	Weight (Kg)	Cutting Increment	LED Spacing	Backing Color	Material	Color Temperature	Wavelength	Beam Angle	Brightness	Color Rendering Index (CRI)	Current (A/5m)	Power Consumption (w/5m)	Power Consumption (w/ft)	Density (LEDs/m)	LED Chip Size	Dimmable	Warranty	Average Life	IP Rating	Compliance	Description	Cut Sheet link
	QolorFLEX® LED Tape, 12V Indoor, Cool White (Medium Output, 515 lumens/metre)	5050-12-CW-30-5-20-1	12VDC	Indoor	Cool White	5m (16.404 ft)	10mm (0.394 in)	0.14 Kg	100.00 mm (3.94 in)	33.4mm (1.31 in)	White	LED Tape	6500° K	N/A	120°	515 lumens/m	70	2.1A	25 w/5m	1.54 w/ft	30 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, Cool White (Medium Output, 515 lumens/metre) (P/N 5050-12-CW-30-5-20-1) is an interior grade LED Tape with a medium output (515 lumens/metre) brightness. The cool white color (6500°K) is suited for enhancing the blue color range.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-cw-30-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Indoor, Cool White (Medium Output, 340 lumens/metre)	3528-12-CW-60-5-20-1	12VDC	Indoor	Cool White	5m (16.404 ft)	10mm (0.394 in)	0.14 Kg	50.0 mm (1.965 in)	16.7mm (0.657 in)	White	LED Tape	6500° K	N/A	120°	340 lumens/m	70	2.0A	24 w/5m	1.46 w/ft	60 LEDs/m	3528	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, Cool White (Medium Output, 340 lumens/metre) (P/N 3528-12-CW-60-5-20-1) is an interior grade LED Tape with a medium output (340 lumens/metre) brightness. The cool white color (6500°K) is suited for enhancing the blue color range.	https://www.citytheatrical.com/docs/default-source/cut-sheets/3528-12-cw-60-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Indoor, Cool White (Medium Low Output, 170 lumens/metre)	3528-12-CW-30-5-20-1	12VDC	Indoor	Cool White	5m (16.404 ft)	10mm (0.394 in)	0.14 Kg	100.00 mm (3.94 in)	33.4mm (1.31 in)	White	LED Tape	6500° K	N/A	120°	170 lumens/m	70	1.0A	12 w/5m	0.73 w/ft	30 LEDs/m	3528	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, Cool White (Medium Low Output, 170 lumens/metre) (P/N 3528-12-CW-30-5-20-1) is an interior grade LED Tape with a medium low output (170 lumens/metre) brightness. The cool white color (6500°K) is suited for enhancing the blue color range.	https://www.citytheatrical.com/docs/default-source/cut-sheets/3528-12-cw-30-5-20-1-cut-sheet.pdf
QolorFLEX® Natural White LED Tape, 12V Indoor:																													
	QolorFLEX® LED Tape, 12V Indoor, Natural White (High Output, 990 lumens/metre)	5050-12-NW-60-5-20-1	12VDC	Indoor	Natural White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	50.0 mm (1.965 in)	16.7mm (0.657 in)	White	LED Tape	4100° K	N/A	120°	990 lumens/m	70	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, Natural White (High Output, 990 lumens/metre) (P/N 5050-12-NW-60-5-20-1) is an interior grade LED Tape with a high output (990 lumens/metre) brightness. The natural white color (4100°K) makes it perfect for displays or light box use, where good color rendition is needed.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-nw-60-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Indoor, Natural White (Medium Output, 495 lumens/metre)	5050-12-NW-30-5-20-1	12VDC	Indoor	Natural White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	100.00 mm (3.94 in)	33.4mm (1.31 in)	White	LED Tape	4100° K	N/A	120°	495 lumens/m	70	2.1A	25 w/5m	1.54 w/ft	30 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, Natural White (Medium Output, 495 lumens/metre) (P/N 5050-12-NW-30-5-20-1) is an interior grade LED Tape with a medium output (495 lumens/metre) brightness. The natural white color (4100°K) equally compliments reds greens and blues.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-nw-30-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Indoor, Natural White (Medium Output, 330 lumens/metre)	3528-12-NW-60-5-20-1	12VDC	Indoor	Natural White	5m (16.404 ft)	8mm (0.31 in)	0.12 Kg	50.0 mm (1.965 in)	16.7mm (0.657 in)	White	LED Tape	4100° K	N/A	120°	330 lumens/m	70	2.0A	24 w/5m	1.46 w/ft	60 LEDs/m	3528	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, Natural White (Medium Output, 330 lumens/metre) (P/N 3528-12-NW-60-5-20-1) is an interior grade LED Tape with a medium output (330 lumens/metre) brightness. Intended for applications where high light output is not required, the natural white color (4100°K) is ideal for use where good color rendition is needed.	https://www.citytheatrical.com/docs/default-source/cut-sheets/3528-12-nw-60-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Indoor, Natural White (Medium Low Output, 165 lumens/metre)	3528-12-NW-30-5-20-1	12VDC	Indoor	Natural White	5m (16.404 ft)	8mm (0.31 in)	0.12 Kg	100.00 mm (3.94 in)	33.4mm (1.31 in)	White	LED Tape	4100° K	N/A	120°	165 lumens/m	70	1.0A	12 w/5m	0.73 w/ft	30 LEDs/m	3528	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, Natural White (Medium Low Output, 165 lumens/metre) (P/N 3528-12-NW-30-5-20-1) is an interior grade LED Tape with a medium/low output (165 lumens/metre) brightness. Intended for applications where high light output is not required, the natural white color (4100°K) is ideal for use where good color rendition is needed.	https://www.citytheatrical.com/docs/default-source/cut-sheets/3528-12-nw-30-5-20-1-cut-sheet.pdf
QolorFLEX® Warm White LED Tape, 12V Indoor:																													
	QolorFLEX® LED Tape, 12V Indoor, Warm White (High Output, 900 lumens/metre)	5050-12-WW-60-5-20-1	12VDC	Indoor	Warm White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	50.0 mm (1.965 in)	16.7mm (0.657 in)	White	LED Tape	2700° K	N/A	120°	900 lumens/m	70	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, Warm White (High Output, 900 lumens/metre) (P/N 5050-12-WW-60-5-20-1) is an interior grade LED Tape with a high output (900 lumens/metre) brightness. The warm white color (2700°K) makes it useful for enhancing skin tones.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-ww-60-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Indoor, Warm White (Medium Output, 450 lumens/metre)	5050-12-WW-30-5-20-1	12VDC	Indoor	Warm White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	100.00 mm (3.94 in)	33.4mm (1.31 in)	White	LED Tape	2700° K	N/A	120°	450 lumens/m	70	2.1A	25.2 w/5m	1.54 w/ft	30 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, Warm White (Medium Output, 450 lumens/metre) (P/N 5050-12-WW-30-5-20-1) is an interior grade LED Tape with a medium output (450 lumens/metre) brightness. The warm white color (2700°K) makes it suited for enhancing skin tones.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-ww-30-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Indoor, Warm White (Medium Output, 300 lumens/metre)	3528-12-WW-60-5-20-1	12VDC	Indoor	Warm White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	50.0 mm (1.965 in)	16.7mm (0.657 in)	White	LED Tape	2700° K	N/A	120°	300 lumens/m	70	2.0A	24 w/5m	1.46 w/ft	60 LEDs/m	3528	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, Warm White (Medium Output, 300 lumens/metre) (P/N 3528-12-WW-60-5-20-1) is an interior grade LED Tape with a medium low output (300 lumens/metre) brightness and a warm 2700°K color temperature.	https://www.citytheatrical.com/docs/default-source/cut-sheets/3528-12-ww-60-5-20-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Indoor, Warm White (Medium Low Output, 150 lumens/metre)	3528-12-WW-30-5-20-1	12VDC	Indoor	Warm White	5m (16.404 ft)	10mm (0.394 in)	0.12 Kg	100.00 mm (3.94 in)	33.4mm (1.31 in)	White	LED Tape	2700° K	N/A	120°	150 lumens/m	70	1.0A	24 w/5m	0.73 w/ft	30 LEDs/m	3528	Fully Dimmable	Two years	25,000 hours	IP20	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Indoor, Warm White (Medium Low Output, 150 lumens/metre) (P/N 3528-12-WW-30-5-20-1) is an interior grade LED Tape with a medium low output (150 lumens/metre) brightness in a warm 2700°K color temperature.	https://www.citytheatrical.com/docs/default-source/cut-sheets/3528-12-ww-30-5-20-1-cut-sheet.pdf
12V Outdoor:																													
QolorFLEX® LED Tape, 12V Outdoor:																													
	QolorFLEX® LED Tape, 12V Outdoor, RGB and Amber	5050-12-RGBA-60-5-67-1	12VDC	Outdoor	RGB & Amber	5m (16.404 ft)	12.2mm (0.48 in)	0.26 Kg	100.00 mm (3.94 in)	16.7mm (0.657 in)	White	Silicone sleeve	N/A	622/518/468/588	120°	400 lumens/m	N/A	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP67	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Outdoor, RGB and Amber (P/N 5050-12-RGBA-60-5-67-1) is an exterior grade hybrid RGB and Amber LED Tape with a medium output brightness and the ability to create a full spectrum of colors when used with a DMX control system.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-rgba-60-5-67-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Outdoor, RGB	5050-12-RGB-60-5-67-1	12VDC	Outdoor	RGB	5m (16.404 ft)	12.2mm (0.48 in)	0.26 Kg	50.0 mm (1.965 in)	16.7mm (0.657 in)	White	Silicone sleeve	N/A	622/518/468	120°	350 lumens/m	N/A	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP67	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Outdoor, RGB (P/N 5050-12-RGB-60-5-67-1) is an exterior grade Red + Green + Blue LED Tape with a high output brightness and the ability to create a wide spectrum of colors when used with a DMX color control system.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-rgb-60-5-67-1-cut-sheet.pdf

QolorFLEX LED Tape Specifications

Product Image	Product Name	Part Number	Operating Voltage	Use Environment	Color(s)	Length	Width	Weight (Kg)	Cutting Increment	LED Spacing	Backing Color	Material	Color Temperature	Wavelength	Beam Angle	Brightness	Color Rendering Index (CRI)	Current (A/5m)	Power Consumption (w/5m)	Power Consumption (w/ft)	Density (LEDs/m)	LED Chip Size	Dimmable	Warranty	Average Life	IP Rating	Compliance	Description	Cut Sheet link
	QolorFLEX® LED Tape, 12V Outdoor, Cool White	5050-12-CW-60-5-67-1	12VDC	Outdoor	Cool White	5m (16.404 ft)	12.2mm (0.48 in)	0.26 Kg	50.0 mm (1.965 in)	16.7mm (0.657 in)	White	Silicone sleeve	6500° K	N/A	120°	1030 lumens/m	70	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP67	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Outdoor, Cool White (P/N 5050-12-CW-60-5-67-1) is an exterior grade LED tape with a high output (1030 lumens/metre) brightness. The cool white color (6500°K) accentuates blues and subdues greens and reds.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-cw-60-5-67-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Outdoor, Natural White	5050-12-NW-60-5-67-1	12VDC	Outdoor	Natural White	5m (16.404 ft)	12.2mm (0.48 in)	0.26 Kg	50.0 mm (1.965 in)	16.7mm (0.657 in)	White	Silicone sleeve	4100° K	N/A	120°	990 lumens/m	70	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP67	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Outdoor, Natural White (P/N 5050-12-NW-60-5-67-1) is an exterior grade LED tape with a high output (990 lumens/metre) brightness.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-nw-60-5-67-1-cut-sheet.pdf
	QolorFLEX® LED Tape, 12V Outdoor, Warm White	5050-12-WW-60-5-67-1	12VDC	Outdoor	Warm White	5m (16.404 ft)	12.2mm (0.48 in)	0.26 Kg	50.0 mm (1.965 in)	16.7mm (0.657 in)	White	Silicone sleeve	2700° K	N/A	120°	900 lumens/m	70	4.2A	50.4 w/5m	3.07 w/ft	60 LEDs/m	5050	Fully Dimmable	Two years	25,000 hours	IP67	ETL, CE, RoHS	QolorFLEX LED Tape, 12V Outdoor, Warm White (P/N 5050-12-WW-60-5-67-1) is an exterior grade LED tape with a high output (900 lumens/metre) brightness.	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-12-ww-60-5-67-1-cut-sheet.pdf
5V Indoor and Outdoor:																													
QolorPIX® Pixel Controlled LED Tapes:																													
	QolorPIX® Pixel Controlled LED Tape, IP20-Rated for Indoor Use	Q5050-5-RGB-48-5-2-0-2	5VDC	Indoor	RGB	5m (16.404 ft)	12mm (0.48 in)	0.24 Kg	21.0mm (0.827 in)	21.0mm (0.827 in)	Black	Pixel Tape	N/A	622/523/467 nm	120°	N/A	N/A	5A	25 w/5m	1.54 w/ft	48 LEDs/m	5050	Fully Dimmable	Two years	50,000 hours	IP20	ETL, CE, RoHS	QolorPIX Pixel Controlled LED Tape (P/N Q5050-5-RGB-48-5-67-2) is designed for the most demanding professional applications. Each reel of tape includes a soldered-on four-pin XLR connector on one end, creating a plug and play connection to the QolorPIX Tape Controller, Eight Output (P/N 5850).	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-5-rgb-48-5-20-2-qolorpix-pixel-tape-in-door.pdf
	QolorPIX® Pixel Controlled LED Tape, IP67-Rated for Outdoor Use	Q5050-5-RGB-48-5-6-7-2	5VDC	Outdoor	RGB	5m (16.404 ft)	14.3mm (0.563 in)	0.24 Kg	21.0mm (0.827 in)	21.0mm (0.827 in)	Black	Silicone sleeve	N/A	622/523/467 nm	120°	N/A	N/A	5A	25 w/5m	1.54 w/ft	48 LEDs/m	5050	Fully Dimmable	Two years	50,000 hours	IP67	ETL, CE, RoHS	QolorPIX Pixel Controlled LED Tape (P/N Q5050-5-RGB-48-5-67-2) is designed for the most demanding professional applications. Each reel of tape includes a soldered-on four-pin XLR connector on one end, creating a plug and play connection to the QolorPIX Tape Controller, Eight Output (P/N 5850).	https://www.citytheatrical.com/docs/default-source/cut-sheets/5050-5-rgb-48-5-67-2-qolorpix-pixel-controlled-led-tape-cut-sheet.pdf