




QolorFLEX LED Tape, RGBNW, 12V Indoor (P/N 5050-12-RGBNW-60-5-20-1) is an interior grade hybrid LED Tape with a high output brightness and the ability to create a full spectrum of colors when used with a DMX control system. The combination of RGB and natural white LEDs allow for precise color mixing for on camera, in studio and theatrical applications. Each LED tape comes with wiring leads on both ends and durable 3M adhesive backing. It is available in full five meter reels and sample strips. 12mm (0.47 in) 16.7mm (0.657 in) LED Spacing Cutting Increment: 100.00mm (3.94 in)



(To scale)

# **QolorFLEX® LED TAPE, RGBNW,** 12V Indoor P/N 5050-12-RGBNW-60-5-20-1

## SPECIFICATIONS:

Physical		
Length	5m	(16.404 ft)
Width	12mm	(0.47 in)
Cutting Increment	100.00 mm	(3.94 in)
LED Spacing	16.7mm	(0.657 in)
Backing Color	White	

Output	
Color(s)	RGB & Natural White
Color Temperature	N/A
Wavelength	622/518/468/4100°K
Beam Angle	120°
Brightness	400 lumens/m
Color Rendering Index (CRI)	N/A

Electrical	
Operating Voltage	12VDC
Current	4.2A
Power Consumption (w/5m)	50.4 w/5m
Power Consumption (w/ft)	3.07 w/ft
Density	60 LEDs/m
LED Chip Size	5050

Product Information	
Use Environment	Indoor
Dimmable	Fully Dimmable
Average Life	25,000 hours
Warranty	Two years
IP Rating	IP20
Compliance	ETL, CE, RoHS







# **QolorFLEX LED Tape Accessories**



### **Ribbon Cables:**

P/N	NAME	
6607	Ribbon Cable, Six	
	Conductor, 18 GA	
6600	Ribbon Cable, Five	
	Conductor, 18 GA	
6600-20	Ribbon Cable, Five	
	Conductor, 20 GA	
	(thinner than 18 GA)	
6608	Ribbon Cable, Four	
	Conductor, 18 GA	
6606	Ribbon Cable, Three	
	Conductor, 18 GA	
6605	Ribbon Cable, Two	
	Conductor, 18 GA	

#### **Connectors:**

P/N	NAME	
6612	Terminal Block Connector, Six Pin, Male	bearing.
6613	Terminal Block Connector, Six Pin, Female	ca a ca a
6610	Terminal Block Connector, Five Pin, Male	FARA A
6611	Terminal Block Connector, Five Pin, Female	Second Control of the
5673	Terminal Block Connector, Four Pin Male	****
5674	Terminal Block Connector, Four Pin Female	
5671	Terminal Block Connector, Three Pin Male	Trans.
5672	Terminal Block Connector, Three Pin Female	2010
5657	Terminal Block Connector, 2-Pin Male	
5658	Terminal Block Connector, 2-Pin Female	
6615	Female barrel to screw terminal connector	
6616	Male barrel to screw terminal connector	FE Million

### **Extrusions and Diffusers:**

P/N	NAME
6693	Aluminum Extrusion, 45-Degree, 2m for 45-Degree LED Tape installations
6694	Diffuser for 45-Degree Extrusion, 2m
6695	Diffuser for Low Profile Extrusion, 2m
6690	Aluminum Extrusion, Low Profile, 2m

## **End Caps, Tape, and Tape Clips:**

	- , - ,
P/N	NAME
6690-1	End Cap for 6690 Aluminum Extrusion.
	Sold in packs of 10.
6690-2	End Cap with hole for 6690 Extrusion.
	Sold in packs of 10.
	Waterproof End Caps for Outdoor-rated
	LED tapes. Sold in packs of 10. Sizes:
6680	9mm w/ 2 holes
6682	8mm (no holes)
6684	12mm w/ 4 holes
6686	12mm (no holes)
6625	3M VHB Double Sided
	Tape Roll, 72 yards
6630	Outdoor Tape Clips and Screws.
	Sold in packs of 12.

# **QolorFLEX Connect 10**

P/N 5748



QolorFLEX Connect 10 is a practical and time saving solution for managing the multiple wire runs and numerous connections needed for large scale installations of LED tape.

Developed to complement QolorFLEX 5-in-1 LED Tape, QolorFLEX Connect 10 is a "plug-in box" that can connect up to nine runs of five, four, three, dual, or single color LED tape to a low voltage low dimmer. Each QolorFLEX Connect 10 uses 10 six position detachable Phoenix terminal block connectors to achieve a quick and well-ordered installation. QolorFLEX Connect 10 is constructed with a Nema 4 IP 20 steel enclosure, and offers a maximum current per device of 40A and maximum load per terminal of 20A.