

# CITY THEATRICAL

NEW YORK • LONDON

475 Barell Ave., Carlstadt, NJ 07072  
Voice: 800-230-9497, 201-549-1160  
Fax: 201-549-1161

## SHoW DMX Vero Net™ Transceiver with Maximum Bandwidth Technology™

The 7400-5708 SHoW DMX Vero Net is the outdoor use version of the SHoW DMX Neo Transceiver. It offers all of the Neo functionality and Ethernet Gateway features in a NEMA 4 / IP 66 package, with a simplified user interface, optimized for permanent installation.

### Wireless DMX Features

- SHoW DMX Neo Mode
  - DMX Synchronized Hopping
  - Ultra Low Latency
  - User selectable Full, Limited or Maximum Bandwidth
  - User selectable Full or Limited Burst
  - User selectable Output Power
  - Lost Data Replacement
  - Advanced High Speed RDM functions
  - Supports reduced DMX slot frames for higher refresh rates
  
- SHoW DMX Neo Adaptive Mode
  - DMX Synchronized Hopping
  - Adaptive Frequency Hopping
  - Ultra Low Latency
  - Adaptive Modified Full Bandwidth
  - User selectable Output Power
  - Lost Data Replacement
  - Advanced High Speed RDM functions
  - Supports reduced DMX slot frames for higher refresh rates
  
- SHoW DMX Classic Mode
  - Communicates with original SHoW DMX equipment
  - DMX Synchronized Hopping
  - User selectable Full or Limited Bandwidth
  - User selectable Full or Limited Burst
  - User selectable Output Power



### RDM Features

- Supports any RDM controller or RDM enabled console
- Fast and reliable wireless RDM Proxy and Responder functions

### Electronic / Functional Features

- DMX In and Out via 3P Screw Terminal
- USB Port
- Ethernet Port via RJ 45 Jack
  - Supports multiple Ethernet show control protocols including sACN, Art-Net, and KiNet
- User Interface

- 3 x ROTARY Switches for SHoW ID entry
  - 5P DIP Switch for configuration
- 100-240 VAC 50/60 Hz 3W Mains Power Input via 3P Screw Terminal

**Construction:** NEMA 4 / IP 66 Aluminum enclosure

**Compliance**

- CE Certified
- IC Certified SHoW DMX Neo Radio Module
- FCC Certified
- RoHS Compliant
- ETL Listed

**CTI Part #:** 7400-5708

**Dimensions:** 7.75"W / 196mm x 8.75" / 222mm H x 4" / 102mm D

**Weight:** 2.6 lbs / 1.18 Kilos

**Accessories:**

- Mounting Bracket (provided)
- 5732 4.5dBi Outdoor Omni-directional Antenna (provided)
- 5632 8dBi Panel Antenna
- 5634 10dBi Yagi Antenna
- 5636 14dBi Yagi Antenna
- 5637 Antenna Splitter
- 5639 Gender Changer